

**Hallowell®**  
**Uniform Exchange Series**  
**8-Person Hanging Garment Lockers**

**General:** Lockers shall Be "Uniform Exchange Series, 8-Person Hanging Garment Lockers" as manufactured by Hallowell, Div. List Industries Inc. or approved equal. Fabricate lockers square, rigid and without warp, with metal faces flat and free from dents or distortion. Make all exposed metal edges safe to touch. Weld frame members together to form rigid, one-piece structure. Weld, bolt, or rivet other joints and connections as standard with manufacturer. Grind exposed welds flush. Do not expose bolts or rivet heads on fronts of locker doors or frames except for fastening of number plates.

Lockers shall be **GREENGUARD Children & Schools Certified<sup>SM</sup>**

**Finishing:** All locker parts to be cleaned and coated after fabrication with a seven-stage hot-spray washing process and coated with a zirconium-based nanoceramic conversion coating providing a green alternative to traditional iron phosphate followed by a coat of high-grade custom blend powder electrostatically sprayed and baked at 350 degrees Fahrenheit for a minimum of 20 minutes to provide a tough durable finish. Color: Gray

**Frame:** Fabricate of 16 gauge (minimum) channels, with integral continuous door stop/strike formed on both latch and hinge side vertical members.

**Master Access Door:** Door to be fabricated from single sheet prime 16 gauge with single bends at top, bottom and double-bends at the sides. Patron doors shall be ventilated with 3" louvers.

**Patron Access Doors:** Doors to be fabricated from single sheet prime 20 gauge with single bends at top, bottom and sides. Patron doors shall be ventilated with 3" louvers.

**Latch Assembly:** The latching mechanism for the access door shall be a multi-point latching system. Locking device shall be designed for use with a padlock. Latch hooks shall be securely welded to the vertical frame channel on the strike side to engage the lock bar.

**Door Hinges:** Shall be a continuous piano hinge securely welded to the door and riveted to the frame.

**Body:** Fabricate back, dividers and sides of 24 gauge (minimum) sheet steel, with double flanged connections extending full height. Back to be ventilated with a ½" diameter hole pattern. Top, bottom and intermediate tier dividers of 21 gauge (minimum) sheet steel with single return bends at all sides.

**Equipment:** Coat rod in each patron opening.

**Locks:** Prepared for padlock (by others).

**One-Year Warranty:** Hallowell Uniform Exchange lockers are covered against all defects in materials and workmanship excluding finish, damage resulting from deliberate destruction and vandalism under this section for a period of one year.